



## TROJAN<sup>TM</sup> T2

- Sophisticated Digital Label Mini Press
- Print Labels 2" – 8.8" Wide

- Fast print speed up to 12 inches per second (60 ft per minute)
- Superior print resolution up to 1600 dpi
- Print width 2" to 8.8"
- World's first affordable production digital label mini press

***"After installation, the Trojan2 has been functioning flawlessly. Unique software interface and user friendliness made our operators smile from day one."***

*- Amarilio Botas, Owner,  
Etipress | Portugal*

## Professional Digital Label Press For Affordable High Volume Label Production

The T2 is the world's first affordable production digital label mini press with numerous advantages for in-house labeling. It is an ideal solution for label converters, print shops, contract packaging solutions and secondary label logistics. With all the characteristics of a much larger and more expensive press, the T2 was created for companies interested in converting their own labels at a fraction of the cost.

The T2 is able to produce large volumes, with automatic tension control, self-maintenance, and sophisticated algorithms. Other features include full-bleed, die cut print capability and integrated web cleaner. The T2 is easy to work with, providing perfect registration, a cost calculator, and TrojanControl touch screen with a job library. While very quiet during operation, the T2 is a robust system with a low cost of ownership providing peace of mind and high quality output.

# Trojan T2 Specifications

## Operation:

<b>Ink Type:</b>	Dye ink, (4) individual CMYK tanks
<b>Print Resolution:</b>	1600 x 1600 dpi full color
<b>Print Speed:</b>	6 ips (152 mm/sec) or 12 ips (305 mm/sec)
<b>Print Area:</b>	Width: 2" (51 mm) – 8.8" (223 mm) Length: 0.4" (10 mm) – 60" (1525 mm), unlimited stitched
<b>Media Sensors:</b>	Optical tracking edge sensor, adjustable position Black mark sensor, gap sensor and continuous
<b>Connectivity:</b>	Ethernet 10/100
<b>Software:</b>	TrojanControl Software Microsoft Windows® 10, 8, 7; Windows Server® 2012, 2008, 64/32-bit Drivers

## Environmental & Physical:

<b>Printer Operating:</b>	Operation: 41° F to 95° F (5° C to 35° C), 59° F (15° C) recommended, at RH 22 to 80% (non-condensing) Storage: 23° F to 122° F (-5° C to 50° C) at RH up to 85%, non-condensing at 149° F (65° C)
<b>Power Requirements:</b>	100-240V AC – 50/60 Hz
<b>Power Consumption:</b>	400W (at peak operation)
<b>Dimensions:</b>	59" L x 36" W x 62" H (1500 mm x 916.5 mm x 1591 mm)
<b>Touchscreen:</b>	15.6" touchscreen
<b>Weight:</b>	1036 lbs. (470 kg) without supplies
<b>Optional Accessories:</b>	Slitter for die-cut labels (3 knives) Exit feeder for inline placement RIP workflow/color management software Label designer software (Variable data)

## Supplies:

<b>Ink Tanks:</b>	CMYK tanks, 2 Liters each
<b>Maintenance Cartridge:</b>	Maintenance tray with replaceable modules (wiper roller/print head cap)
<b>Ink Type:</b>	High performance, water-based dye inks with extra wide color gamut that produce true-to-life color when combined with QuickLabel approved media

## Labels:

<b>Width:</b>	2" (51 mm) – 9.5" (241 mm)
<b>Length (Die-cut):</b>	0.6" (15 mm) – 60" (1525 mm)
<b>Thickness:</b>	4pt/mil to 12 pt/mil
<b>Roll Size:</b>	Max 24" (600 mm), 3" (76 mm) core
<b>Types:</b>	Paper, Inkjet coated gloss paper, PE, PET, PP

## Warranty:

Printer: 12 Month Manufacturer's Parts & Labor Warranty (excludes wear parts and supplies).



Powered by  memjet.

### Ihr Händler:

**REA Elektronik GmbH**  
Teichwiesenstr. 1  
64367 Mühlthal  
T: +49 (0) 6154 638-0  
F: +49 (0) 6154 638-195  
info@rea-label.de  
www.rea-label.com

**TrojanLabel | Tel: +45 29 64 00 05 | [contact@trojanlabel.com](mailto:contact@trojanlabel.com)**